Rackmount, Click In Support Bar, 48-Port, 2U

Rackmount, Click In Support Bar, 48-Port, 2U

Specifications:

Length: 19"
Width: 3.5"
Height: 8"
Weight: 1.9 lbs
Color/Finish: Black Powder Coated Finish

Key Features:

- Has an open frame design making it easy to reach both levels of cables
- Fits standard 19" racks and enclosures
- Occupies 2U of rack space
- Install 1 Support Bar per 2U Ethernet Patch Panel
- Keep cables neatly organized and supported
- For 48-Port Patch Panels

What's in the Box:

- Qty 1 - Click In Support Bar, 48 Port





Description

This 48-port cable support bar is a perfect accessory to provide additional weight support for a 2U patch panel 48-port. Can also be used for 3U and 4U 48-port patch panels per 2U if desired. Reverse pre-numbering to match front-side left-to-right port patch panel numbering helps simplify and organize cable configuration.

Our 2U Click In Support Bar has a rugged black powder-coat to match your racks and cabinets and pre-numbered 24 cable anchor points for installing cable ties. Keeps rear cables neatly organized and supported ensuring maximum communication performance by minimizing cable movement that may cause cables to wiggle loose.

Rack Accessories

Effective cable organization involves more than just the combination of cable raceway, ladder racks, and server racks. Sometimes it's the little things, like server rack accessories that bring the network components together. We stock an assortment of cable rack accessories including: D-ring cable managers, horizontal and vertical cable managers, cable management duct covers, and cable routing banks, just to name a few.

©2013 CRN Solutions Inc. dba. Primus Cable
All Rights Reserved.

Although Primus Cable makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Primus Cable provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Primus Cable be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Primus Cable has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Primus Cable products are subject to Primus Cable's standard terms and conditions of sale.
Primus Cable believes this product to be in compliance with EU RoHS (Directive 2002/EC, 27 Jan. 2003). Material manufactured prior to the compliance date may be in stock at Primus Cable facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Primus Cable's knowledge, information, and belief at the date any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification and regulations based on their individual usage of the product.

Primus Cable declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC